



PG adapter to solid metal tube

Adapter for connection of solid metal tubes with flexible conduits
High-grade, specially formulated polyamide 6
High conduit pull-out strength
Very good chemical properties
Fits both conduit profiles - fine (T) and coarse (G)
Temperature: – 50 ... + 105 °C
Free from halogens and cadmium
Fits both conduit profiles - fine (T) and coarse (G)

Specification

MATERIAL	Polyamide 6
TEMPERATURE RANGE	-50°C....+105°C
COLOUR	Black

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

ARTICLE NO.	DESCRIPTION	CONDUIT SIZE	L MM	A MM	DI1 MM	DI2 MM	PCS/PACK
BVNR-RE12	PG11	12	54	25	18.5	26	50
BVNR-RE12-24	PG11 with jubilee clip	12	54	25	18.5	26	50
BVNR-RE17	PG16	17	65	28	22.5	30	50
BVNR-RE17-28	PG16 with jubilee clip	17	65	28	22.5	30	50
BVNR-RE23	PG21	23	71	30	28.3	37	30
BVNR-RE23-32	PG21 with jubilee clip	23	71	30	28.3	37	30
BVNR-RE29	PG29	29	70.5	30	37	45	20
BVNR-RE29-44	PG29 with jubilee clip	29	70.5	30	37	45	20
BVNR-RE36	PG36	36	84.5	30	47	56	20
BVNR-RE36-50	PG36 with jubilee clip	36	84.5	30	47	56	20
BVNR-RE48	PG48	48	90	35	59.3	67.5	10
BVNR-RE48-65	PG48 with jubilee clip	48	90	35	59.3	67.5	10

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö