



## T-connection IP66

- For industry and machine building.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMA conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G).

## Specification

<b>MATERIAL</b>	Polyamide PA6
<b>INGRESS PROTECTION</b>	IP66 stat. / IP54 dyn.
<b>TEMPERATURE RANGE</b>	-40°C....+105°C
<b>COLOUR</b>	Black RAL 9005
<b>HALOGEN-FREE</b>	Yes

## Variants

ARTICLE NO.	CONDUIT SIZE	A MM	B MM	C MM	D MM	H MM	HI MM	EI MM	M	PCS/PACK
BVTD-101010GT	3 x NW 10	39,5	16,0	10,5	21,0	59,0	21	19	2 x M4	50
BVTD-121212GT	3 x NW 12	47,5	18,5	12,0	26,5	71,5	24	22,5	2 x M4	50
BVTD-171717GT	3 x NW 17	61,5	22,0	15,0	34,0	93,5	30	29,5	2 x M5	50
BVTD-232323GT	3 x NW 23	70,0	28,0	19,0	41,5	106,5	37,5	30,5	2 x M5	20
BVTD-292929GT	3 x NW 29	77,5	32,5	22,5	48,0	111	44,5	31,5	2 x M5	20
BVTD-363636GT	3 x NW 36	99,0	40,0	27,5	57,0	150,5	54,5	44	2 x M6	5
BVTD-484848GT	3 x NW 48	111,5	47,5	33,5	71,0	163,0	66,5	43	2 x M6	5