



# T-connection IP66

- For industry and machine building.
- High-grade, specially formulated polyamide 6.
- Very high impact resistance.
- Vibration-proof connection to PMA conduits.
- Easy installation: simply push the conduit in.
- High conduit pull-out strength.
- Can be easily re-opened with a screwdriver.
- Very good chemical properties.
- Free from halogens and cadmium.
- Fits both conduit profiles - fine (T) and coarse (G).

## Specification

| | |
|---|---|
| **MATERIAL** | Polyamide PA6 |
| **INGRESS PROTECTION** | IP66 stat. / IP54 dyn. |
| **TEMPERATURE RANGE** | -40°C....+105°C |
| **COLOUR** | Black RAL 9005 |
| **HALOGEN-FREE** | Yes |



www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

## Variants

| ARTICLE NO. | CONDUIT SIZE | A MM | B MM | C MM | D MM | H MM | H1 MM | E1 MM | M | PCS/PACK |
|---|---|---|---|---|---|---|---|---|---|---|
| BVTD-101010GT | 3 x NW 10 | 39,5 | 16,0 | 10,5 | 21,0 | 59,0 | 21 | 19 | 2 x M4 | 50 |
| BVTD-121212GT | 3 x NW 12 | 47,5 | 18,5 | 12,0 | 26,5 | 71,5 | 24 | 22.5 | 2 x M4 | 50 |
| BVTD-171717GT | 3 x NW 17 | 61,5 | 22,0 | 15,0 | 34,0 | 93,5 | 30 | 29.5 | 2 x M5 | 50 |
| BVTD-232323GT | 3 x NW 23 | 70,0 | 28,0 | 19,0 | 41,5 | 106,5 | 37.5 | 30.5 | 2 x M5 | 20 |
| BVTD-292929GT | 3 x NW 29 | 77,5 | 32,5 | 22,5 | 48,0 | 111 | 44.5 | 31.5 | 2 x M5 | 20 |
| BVTD-363636GT | 3 x NW 36 | 99,0 | 40,0 | 27,5 | 57,0 | 150,5 | 54.5 | 44 | 2 x M6 | 5 |
| BVTD-484848GT | 3 x NW 48 | 111,5 | 47,5 | 33,5 | 71,0 | 163,0 | 66.5 | 43 | 2 x M6 | 5 |



www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö