Multibox, fire resistant

Specification

INFORMATION_KLIKSEAL

- Up to 90 minutes fire resistant
- Approved acc. to. EN 13501-2:2007+A1:2009 and EN 1363-1:2012
- Fitted with integral, smoothly hinging combi conduit lead-ins
- Drillhole 76mm
- Fitted with 2 conical conduit lead-ins with integral click conection for both 16 and 20mm conduits, one of which is sealed with a knocj-out
- Anchored firmly in the wall by the metal screw fastening plates with three threads
- No gap between the switch plate and wall due to the extremely thin sturdy rim of the metal fastening sets
- Extra feed-through possibility for coupled boxes
- Attachment screws: M3

Download test report >>

MATERIAL	Polyethylene PE-HD
GLOW WIRE TEST	850°C
HALOGEN-FREE	Yes

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö

Variants

E-NUMBER	DESCRIPTION	PCS/PACK	BVB
1426129	Fire resistant Multibox with hinging combi conduit lead-ins	1/25	

www.rutab.com Tel: +46 380 - 55 50 50 info@rutab.se Lerbacksgatan 2, 571 38 Nässjö