



HaloX 100 Housing with Tunnel 190mm & Frontpart with fibreboard

for on-site mixed concrete

HaloX® for on-site mixed concrete. The versatile system with a range of different front rings enables the planning and use of virtually any lighting and speaker manufacturer, regardless of whether the shape is round or square.

- Toolless combination entry for M20/M25 conduits
- Conduit entry limitation to prevent the need to shorten the conduit inside
- No reinforcement cuts in tunnel section area
- Universal front part with fibreboard for luminaires and speakers with hole diameter and Ø0-100mm.

Specification

| | |
|-------------------------|-----------------------|
| CEILING EXIT (CE) Ø | 0-100mm |
| MAX. INSTALLATION DEPTH | 110mm |
| WATTAGE MAX. | LED 20W / Halogen 50W |
| EXTERNAL Ø MM | 130 |
| DEPTH INCL. FRONT PART | 120mm |
| TUNNEL LENGTH | 190mm |
| TUNNEL WIDTH | 140mm |
| TUNNEL HEIGHT | 85mm |
| ENTRY | 2 |

Variants

| E-NUMBER | ARTICLE NO. | DESCRIPTION | PCS/PACK | BVB |
|----------|-------------|---|----------|---|
| 1420803 | 1281-72 | HaloX 100 Housing with Tunnel 190mm & Frontpart with fibreboard | 10 |  |