



MCB 1-pole Type B

- Semko approved - Ref no 1621033
- Function of isolation acc. to IEC 60947-2
- Contact position indication
- Fork / Pin connection for Busbars
- D-characteristic on request

Specification

RATED VOLTAGE	230/400V AC
RATED SHORT-CIRCUIT CAPACITY ICN	10kA
RATED FREQUENCY	50/60Hz
ENERGY LIMITING CLASS	3
ELECTRO-MECHANICAL ENDURANCE	8000 cycles
CONNECTION CAPACITY	1 - 25 mm ²
FASTENING TORQUE	2,0 Nm
INSTALLATION	DIN rail 35 mm
TEMPERATURE RANGE	-5°C.....+40°C
INGRESS PROTECTION	IP20
STANDARDS	EN 60898-1:2003+A1+A11+A12+A13

Variants

E-NUMBER	ARTICLE NO.	KARAKTERISTIK	RATED CURRENT (A)	PCS/PACK
2146301	RSB-101	B	1	12/120
2146302	RSB-102	B	2	12/120
2146303	RSB-103	B	3	12/120
2146304	RSB-104	B	4	12/120
2146306	RSB-106	B	6	12/120
2146307	RSB-110	B	10	12/120
2146308	RSB-113	B	13	12/120
2146309	RSB-116	B	16	12/120
2146310	RSB-120	B	20	12/120
2146311	RSB-125	B	25	12/120
2146312	RSB-132	B	32	12/120
2146313	RSB-140	B	40	12/120
2146314	RSB-150	B	50	12/120
2146315	RSB-163	B	63	12/120