



MCB 2-pole Type B

- Semko approved - Ref no 1621033
- Function of isolation acc. to IEC 60947-2
- Contact position indication
- Fork / Pin connection for Busbars
- D-characteristic on request

Specification

RATED VOLTAGE	230/400V AC
RATED SHORT-CIRCUIT CAPACITY ICN	10kA
RATED FREQUENCY	50/60Hz
ENERGY LIMITING CLASS	3
ELECTRO-MECHANICAL ENDURANCE	8000 cycles
CONNECTION CAPACITY	1 - 25 mm ²
FASTENING TORQUE	2,0 Nm
INSTALLATION	DIN rail 35 mm
TEMPERATURE RANGE	-5°C....+40°C
INGRESS PROTECTION	IP20
STANDARDS	EN 60898-1:2003+A1+A11+A12+A13

Variants

E-NUMBER	ARTICLE NO.	KARAKTERISTIK	RATED CURRENT (A)	PCS/PACK
2146317	RSB-201	B	1	6/60
2146318	RSB-202	B	2	6/60
2146319	RSB-203	B	3	6/60
2146320	RSB-204	B	4	6/60
2146322	RSB-206	B	6	6/60
2146323	RSB-210	B	10	6/60
2146324	RSB-213	B	13	6/60
2146325	RSB-216	B	16	6/60
2146326	RSB-220	B	20	6/60
2146327	RSB-225	B	25	6/60
2146328	RSB-232	B	32	6/60
2146329	RSB-240	B	40	6/60
2146330	RSB-250	B	50	6/60
2146331	RSB-263	B	63	6/60