



MCB 3-pole Type B

- Semko approved - Ref no 1621033
- Function of isolation acc. to IEC 60947-2
- Contact position indication
- Fork / Pin connection for Busbars
- D-characteristic on request.

Specification

RATED VOLTAGE	230/400V AC
RATED SHORT-CIRCUIT CAPACITY ICN	10kA
RATED FREQUENCY	50/60Hz
ENERGY LIMITING CLASS	3
ELECTRO-MECHANICAL ENDURANCE	8000 cycles
CONNECTION CAPACITY	1 - 25 mm ²
FASTENING TORQUE	2,0 Nm
INSTALLATION	DIN rail 35 mm
TEMPERATURE RANGE	-5°C.....+40°C
INGRESS PROTECTION	IP20
STANDARDS	EN 60898-1:2003+A1+A11+A12+A13

Variants

E-NUMBER	ARTICLE NO.	KARAKTERISTIK	RATED CURRENT A	PCS/PACK
2146333	RSB-301	B	1	4/40
2146334	RSB-302	B	2	4/40
2146335	RSB-303	B	3	4/40
2146336	RSB-304	B	4	4/40
2146338	RSB-306	B	6	4/40
2146339	RSB-310	B	10	4/40
2146340	RSB-313	B	13	4/40
2146341	RSB-316	B	16	4/40
2146342	RSB-320	B	20	4/40
2146343	RSB-325	B	25	4/40
2146344	RSB-332	B	32	4/40
2146345	RSB-340	B	40	4/40
2146346	RSB-350	B	50	4/40
2146347	RSB-363	B	63	4/40