



MCB 3-pole Type C

- Semko approved - Ref no 1621033
- Function of isolation acc. to IEC 60947-2
- Contact position indication
- Fork / Pin connection for Busbars
- D-characteristic on request.

Specification

RATED VOLTAGE	230/400V AC
RATED SHORT-CIRCUIT CAPACITY ICN	10kA
RATED FREQUENCY	50/60Hz
ENERGY LIMITING CLASS	3
ELECTRO-MECHANICAL ENDURANCE	8000 cycles
CONNECTION CAPACITY	1 - 25 mm ²
FASTENING TORQUE	2,0 Nm
INSTALLATION	DIN rail 35 mm
TEMPERATURE RANGE	-5°C...+40°C
INGRESS PROTECTION	IP20
STANDARDS	EN 60898-1:2003+A1+A11+A12+A13

Variants

E-NUMBER	ARTICLE NO.	KARAKTERISTIK	RATED CURRENT (A)	PCS/PACK
2146502	RSC-301	C	1	4/40
2146504	RSC-302	C	2	4/40
2146506	RSC-303	C	3	4/40
2146508	RSC-304	C	4	4/40
2146512	RSC-306	C	6	4/40
2146516	RSC-310	C	10	4/40
2146518	RSC-313	C	13	4/40
2146520	RSC-316	C	16	4/40
2146522	RSC-320	C	20	4/40
2146524	RSC-325	C	25	4/40
2146526	RSC-332	C	32	4/40
2146528	RSC-340	C	40	4/40
2146530	RSC-350	C	50	4/40
2146532	RSC-363	C	63	4/40