



PD4N-DALILINK

Specification

MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+55°C
PROTECTION CATEGORY	II
SETTINGS	DALI LINK Bluetooth-app
LIGHT VALUES	10 - 2500 Lux
EXTENSION OF THE DETECTION AREA	with detector in slave mode
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 6.40m tangential 24m radial 8m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light
FOLLOW-UP TIME	1 - 120min.
CHANNEL 1	For light control depending on brightness.
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK	EPD / PEP
1301100	93377	PD4N DALI LINK	IP20	White	1	Yes
1301325	93073	PD4N DALI LINK	-	White	1	
1739249	93307	PD4N DALI LINK	IP54	White	1	
1313699	93164	Wall holder PD2N/PD4N	-	White	1	
1313711	93192	SM socket for Wall holder	-	White	1	