



PD2N-M-DACO DALI-2

Specification

SUPPLY VOLTAGE	230 V / 50 Hz
POWER CONSUMPTION	approx. 2W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
PROTECTION CATEGORY	II
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 4m tangential 10m radial 6m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

For lightning control

DALI output:
80mA (guaranteed, 125mA (max.))

Follow-up time:
1 - 150min

Brightness set value:
10 - 2500 lux

CHANNEL 1

PUSH BUTTON

1 push button

HALOGEN-FREE

Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK	EPD / PEP	BVB
1301599	93452	PD2N-M-DACO DALI-2	IP20	White	1	Yes	
1301616	93454	Förhöjningsram PD2N H	IP54	White	1		
1301369	93067	BLE-IR-Adapter	-	Black	1		
1302173	92122	FJÄRRKONTROLL IR-PD-DALI-E	-	Grey	1		
1301096	92846	Strömförsörjning PS-DALI	IP20	White	1		
1313683	92199	Wire basket BSK	-	White	1		