



PD2N-M-DACO-DUO DALI-2

Specification

SUPPLY VOLTAGE	230 V / 50 Hz
POWER CONSUMPTION	approx. 3W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
INGRESS PROTECTION	IP20
PROTECTION CATEGORY	II
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 4m tangential 10m radial 6m
MOUNTING HEIGHT MIN./MAX./RECOMMENDED	2m / 5m / 2.5m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m

CHANNEL 1

For lightning control

DALI output:
40mA (guaranteed, 60mA (max))

Follow-up time:
1 - 150min

Brightness set value:
10 - 2500 lux

CHANNEL 2

For lightning control

DALI output:
40mA (guaranteed, 60mA (max))

Follow-up time:
1 - 150min

Brightness set value:
10 - 2500 lux

PUSH BUTTON

2 push buttons

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
1303008	93453	PD2N-M-DACO-DUO DALI-2	IP20	White	1
1301616	93454	Förhöjningsram PD2N H	IP54	White	1
1301369	93067		-	Black	1
1302173	92122	FJÄRRKONTROLL IR-PD-DALI-E	-	Grey	1
1301096	92846	Strömförsörjning PS-DALI	IP20	White	1
1313683	92199	Skyddskorg BSK	-	White	1