



## PD4N-M-DACO DALI-2

### Specification

|                                 |  |
|---------------------------------|--|
| SUPPLY VOLTAGE                  | 230 V / 50 Hz  |
| POWER CONSUMPTION               | approx. 2W   |
| MATERIAL ENCLOSURE              | Polycarbonate, UV-resistant  |
| TEMPERATURE RANGE               | -25°C...+50°C  |
| PROTECTION CATEGORY             | II   |
| EXTENSION OF THE DETECTION AREA | with slave detector  |
| AREA OF COVERAGE                | circular 360°  |
| RANGE OF COVERAGE               | Ø H 2.50m / T = 18°C:<br>seated 6.40m<br>tangential 24m<br>radial 8m |
| RECOMMENDED HEIGHT FOR MOUNTING | 2,5m   |
| LIGHT MEASUREMENT               | Mixed light, daylight + artificial light                             |

For lightning control

DALI output:  
80mA (guaranteed, 125mA (max.))

Follow-up time:  
1 - 150min

Brightness set value:  
10 - 2500 lux

**CHANNEL 1**

**PUSH BUTTON**

1 push button

**HALOGEN-FREE**

Yes

## Variants

| E-NUMBER | ARTICLE NO. | DESCRIPTION                | INGRESS PROTECTION | COLOUR | PCS/PACK | EPD / PEP | BVB   |
|----------|-------------|----------------------------|--------------------|--------|----------|-----------|---|
| 1301604  | 93460       | PD4N-M-DACO DALI-2         | IP20               | White  | 1        | Yes       |  |
| 1301369  | 93067       | BLE-IR-Adapter             | -                  | Black  | 1        |           |   |
| 1302173  | 92122       | FJÄRRKONTROLL IR-PD-DALI-E | -                  | Grey   | 1        |           |   |
| 1301096  | 92846       | Strömförsörjning PS-DALI   | IP20               | White  | 1        |           |   |
| 1301325  | 93073       | Korridorlins PD4N Typ A    | IP20               | White  | 1        |           |   |
| 1313683  | 92199       | Wire basket BSK            | -                  | White  | 1        |           |   |
| 1313699  | 93164       | Wall holder PD2N/PD4N      | -                  | White  | 1        |           |   |
| 1313711  | 93192       | SM socket for Wall holder  | -                  | White  | 1        |           |   |
| 1301609  | 93465       | Förhöjningsram PD4N H      | IP54               | White  | 1        |           |   |