



PD4N-M-DACO-DUO DALI-2

Specification

SUPPLY VOLTAGE	230 V / 50 Hz
POWER CONSUMPTION	approx. 3W
TEMPERATURE RANGE	-25°C....+50°C
INGRESS PROTECTION	IP20
PROTECTION CATEGORY	II
AREA OF COVERAGE	circular 360°
MOUNTING HEIGHT MIN./MAX./RECOMMENDED	2m / 10m / 2.5m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
	For lightning control
	DALI output: 40mA (guaranteed, 60mA (max.)
CHANNEL 1	Follow-up time: 1 - 150min
	Brightness set value: 10 - 2500 lux

For lightning control

DALI output:
40mA (guaranteed, 60mA (max))

Follow-up time:
1 - 150min

Brightness set value:
10 - 2500 lux

CHANNEL 2

PUSH BUTTON

2 push buttons

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	INGRESS PROTECTION	COLOUR	PCS/PACK
1303009	93461	PD4N-M-DACO-DUO DALI-2	IP20	White	1
1301369	93067	BLE-IR-Adapter	-	Black	1
1302173	92122		-	Grey	1
1301096	92846	Power consumption PS-DALI	IP20	White	1
1301325	93073	Korridorlins PD4N Typ A	IP20	White	1
1313683	92199	Skyddskorg BSK	IP20	White	1
1301609	93465	Förhöjningsram PD4N H	IP54	White	1