



PD3N-1C (Micro) Till/Från 1-kanalig Akustiksensor

Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0,5W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C....+50°C
PROTECTION CATEGORY	II
SETTINGS	Potentiometers and remote control
LIGHT VALUES	Remote control 20 - 1000 Lux, Potentiometer 10 - 2000 Lux
EXTENSION OF THE DETECTION AREA	Parallel connection with 1-channel motion detectors (max. 8 parallel)
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 4m tangential 10m radial 6m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
FOLLOW-UP TIME	30sec - 30min, pulse
CHANNEL 1	For light control depending on brightness.
RELAY	NOC/with pre-travel tungsten contact

SWITCHING CAPACITY	2300 W, $\cos \varphi = 1$
	1150 VA, $\cos \varphi = 0,5$
	800W LED
	max. startström I_p (20ms) = 165 A max. startström I_p (200µs) = 800 A
DIMENSIONS	H x Ø mm: UTP 53 x 106, TAK 81 x 83
VISIBLE PORTION WHEN BUILT INTO CEILING	H x Ø mm: 20 x 83
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
1313567	92219	PD3-1C-UTP MICRO	UTP Surface	IP44	White	1
1313569	92184	PD3-1C-TAK MICRO	TAK False ceiling	IP23	White	1
1302171	93110	IR-PD3N-4N-1C-E	-	-	Grey	1
1313664	92159	IR-PD-MINI	-	-	Grey	1