



Indoor 140-L med integrerad tryckknapp

Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0.4 W approx. 0.8 W with nightlight
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C....+50°C
PROTECTION CATEGORY	II
SETTINGS	Potentiometers and DIP switches
LIGHT VALUES	Potentiometer 10 - 2000 Lux
EXTENSION OF THE DETECTION AREA	with detector in slave mode
AREA OF COVERAGE	120°
RANGE OF COVERAGE	T = 18°C: tangential max. r 8m radial max. r 3m
RECOMMENDED HEIGHT FOR MOUNTING	1,1m (max. 1,2m)
LIGHT MEASUREMENT	Mixed light, daylight + artificial light
FOLLOW-UP TIME	15sec - 30min
CHANNEL 1	For light control depending on brightness.
RELAY	NOC/with pre-travel tungsten contact
SWITCHING CAPACITY	UppdateringLed10

Variants

E-NUMBER	ARTICLE NO.	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
1300354	94325	INF Flush	IP20	-	1
-	94340	INF Flush	IP20	White RAL 9016	1
-	94341	INF Flush	IP20	Antracit RAL 7021	1
-	94342	INF Flush	IP20	White RAL 9010	1
1300355	94343	INF Flush	IP20	White RAL 9010	1
-	94344	INF Flush	IP20		1