



## Indoor 180-R-11-48V med akustiksensör

### Specification

|                                 |                                                                                               |
|---------------------------------|-----------------------------------------------------------------------------------------------|
| SUPPLY VOLTAGE                  | 11-48VAC/DC                                                                                   |
| POWER CONSUMPTION               | approx. 1W                                                                                    |
| MATERIAL ENCLOSURE              | Polycarbonate, UV-resistant                                                                   |
| TEMPERATURE RANGE               | -25°C....+50°C                                                                                |
| PROTECTION CATEGORY             | II                                                                                            |
| SETTINGS                        | Potentiometers                                                                                |
| LIGHT VALUES                    | Potentiometer 10 - 1200 Lux                                                                   |
| RANGE OF COVERAGE               | T = 18°C:<br>tangential max. r 10m<br>radial max. r 3m                                        |
| RECOMMENDED HEIGHT FOR MOUNTING | 1,1m (max 2,2m)                                                                               |
| LIGHT MEASUREMENT               | Mixed light, daylight + artificial light                                                      |
| FOLLOW-UP TIME                  | 15sec. - 16min. or pulse                                                                      |
| CHANNEL 1                       | For light control depending on brightness.                                                    |
| SWITCHING CAPACITY              | 3A version: 3 A $\cos \varphi = 1$<br>RR version: with Reed-Relay, 100 mA, $\cos \varphi = 1$ |
| PUSH BUTTON                     | 1 push button                                                                                 |
| HALOGEN-FREE                    | Yes                                                                                           |

## Variants

| E-NUMBER | ARTICLE NO. | DESCRIPTION                                            | MOUNTING    | INGRESS PROTECTION | COLOUR               | PCS/PACK |
|----------|-------------|--------------------------------------------------------|-------------|--------------------|----------------------|----------|
| 1313624  | 92666       | Sensorinsats för Indoor 180-R11-48V-3A-INF             | INF Flush   | IP20               | -                    | 1        |
| 1300150  | 92667       | Sensorinsats för Indoor 180-R11-48V-RR-INF             | INF Flush   | IP20               | -                    | 1        |
| 1300533  | 39241       |                                                        | -           | -                  | White RAL 9003       | 1        |
| 1300534  | 39242       |                                                        | -           | -                  | White RAL 9016       | 1        |
| 1300594  | 39222       | Centrumplatta Indoor 180, designkompatibel med ELKO RS | -           | -                  | White RAL 9010       | 1        |
| 1313640  | 92630       | Täckram IP20                                           | INF Flush   | IP20               | White RAL 9010       | 1        |
| N4920135 | 92631       | Täckram IP20                                           | INF Flush   | IP20               | White RAL 9016       | 1        |
| N4920136 | 92632       | Täckram IP20                                           | INF Flush   | IP20               | Cream white, RAL1013 | 1        |
| N4920137 | 92633       | Täckram IP20                                           | INF Flush   | IP20               | Silver RAL 9006      | 1        |
| N4920138 | 92634       | Täckram IP20                                           | INF Flush   | IP20               | Antracit RAL 7021    | 1        |
| 1313641  | 92139       | Täckram IP54                                           | INF Flush   | IP54               | White RAL 9010       | 1        |
| 1313642  | 92141       | Förhöjningsram UTP                                     | UTP Surface | IP44               | White RAL 9010       | 1        |