



PD11-M-1C-FLAT Till/Från

Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	approx. 0,3W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C...+50°C
PROTECTION CATEGORY	II
SETTINGS	Remote control
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2.50m / T = 18°C: seated 3m tangential 9m radial 6m
RECOMMENDED HEIGHT FOR MOUNTING	2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light

Relä för belysningsstyrning NO med pretravel volfram kontakt, ljusreglerad

CHANNEL 1

Belastningsförmåga:

2300 W, $\cos \varphi = 1$

1150 VA, $\cos \varphi = 0,5$

800W LED

max. startström I_p (20ms) = 165 A

max. startström I_p (200 μ s) = 800 A

Tidsinställning: 5 - 30 min, Puls

Ljusvärden:

Potentiometer 20 - 2000 lux

DIMENSIONS	H x \emptyset mm: TAK 60 x 52
VISIBLE PORTION WHEN BUILT INTO CEILING	H x \emptyset mm: 0,85 x 52
PUSH BUTTON	1 push button
HALOGEN-FREE	Yes

Variants

E-NUMBER	ARTICLE NO.	DESCRIPTION	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK	EPD / PEP
1300356	92583		TAK False ceiling	IP20	White	1	Yes
-	92537	Täckring PD11 \emptyset 52mm svart	-	-	Black	1	