



PICO-N-M-1C

Specification

SUPPLY VOLTAGE	110-240VAC / 50-60Hz
POWER CONSUMPTION	0,35W
MATERIAL ENCLOSURE	Polycarbonate, UV-resistant
TEMPERATURE RANGE	-25°C....+50°C
PROTECTION CATEGORY	II
SETTINGS	Remote control
LIGHT VALUES	10 - 2000 Lux
EXTENSION OF THE DETECTION AREA	with slave detector
AREA OF COVERAGE	circular 360°
RANGE OF COVERAGE	Ø H 2,50m / T = 18°C: seated 4m tangential 10m radial 6m
RECOMMENDED HEIGHT FOR MOUNTING	Ceiling: 2,5m
LIGHT MEASUREMENT	Mixed light, daylight + artificial light
FOLLOW-UP TIME	15sec - 30min, pulse
SWITCHING CAPACITY	2300 W, cos φ = 1 1150 VA, cos φ = 0,5 400W LED

PUSH BUTTON

1 push button

HALOGEN-FREE

Yes

Variants

ARTICLE NO.	MOUNTING	INGRESS PROTECTION	COLOUR	PCS/PACK
93159	TAK False ceiling	IP65	White	1
92077	-	-	Grey	1
92159	-	-	Grey	1